



Product technical sheet

MAXX 2612







4 - 14 years

40 kids

188,5 m²

Material specification

- Hot-dip galvanized and powder coated construction of 200 x 120 mm profile,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Transparent polycarbonate panels with a weather-resistant print,
- Covers made of hot-dip galvanized and powder coated steel mesh,
- Side panels made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- Stainless steel tube slide,
- Elements made of safe, certified rubber with textile reinforcement,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development



sliding

passage



community



climbing


















HIC 105

HIC 100



Product technical sheet

MAXX 2612

Product data

Length	1635 cm
Width	1455 cm
Total height	1530 cm
Age group	4 - 14 years
Number of users	40 kids
Safety zone	188,5 m2
Free fall height	110 cm
The height of the platforms	360, 530, 540, 720, 930 cm
tube slide platform height	360, 540, 810, 930 cm
In accordance with norm EN	1176-1:2017+A1:2023
Availability of spare parts	YES

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Durability of steel and 15 stainless steel structural elements



85,9 m²

[SS] 188,5 m²

15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)



5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991





Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Particle size from 20 to 80	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	30	≤200	
	40	≤300	
sand or dravel (A (1)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		110

Product technical sheet

MAXX 2612

Amount of safe surface corresponding with free fall height:

HIC <60	85,9 m ²
HIC 100	64,8 m ²
HIC 105	19,6 m²
HIC 110	18,2 m²

Data is subject to change without prior notice.

