

Product technical sheet

STEEL+ 1708







3 - 14 years

24 kids

40,5 m²





Material specification

- Powder galvanized and powder coated or stainless steel construction of 80 x 80 cm profile,
- Platforms and climbing walls made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE side panels,
- · Fireman's pole made of stainless steel,
- Drawing board made of durable HPL plate, resistant to weather conditions,
- Music panels made of durable HPL plate, resistant to weather conditions,
- Telescope made of stainless steel and durable HDPE plate, resistant to weather conditions,
- Rudder made of durable HDPE plate, resistant to weather conditions,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



Facilitating disability



easy access



integration



Intellectual development



manipulation



music



sight



thinking



Physical development



pull-up climbing



passage

M: +48 793 404 991











Product technical sheet


STEEL+ 1708




5 number of interactive elements



8 number of activity elements







Product data

Length	400 cm	
Width	356 cm	
Total height	373 cm	
Age group	3 - 14 years	
Number of users	24 kids	
Safety zone	40,5 m2	
Free fall height	220 cm	
The height of the platforms	150, 180 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	35 kg	
Dimensions of the largest part	396x8x8 cm	
Availability of spare parts	YES	
Installation time	7,0 h	

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	Particle size from 5	30	≤200
	40	≤300	
sand or dravel (A (1)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	ed Tested according to EN 1177		220

Product technical sheet

STEEL+ 1708

Amount of safe surface corresponding with free fall height:

HIC 100	4,4 m ²
HIC 150	1,0 m ²
HIC 180	12,1 m ²
HIC 200	3,8 m ²
HIC 220	19,2 m²

Data is subject to change without prior notice.

